

DIGIT SMART HT

Battery Powered Strapping Tool For Plastic Strap

The Digit Smart tools are compact, easy to use, and versatile for many strapping applications. The Digit Smart tool incorporates a number of unique features to the tension and sealing areas that allow for precision operation. With minimal adjustments, the Digit Smart tool can be used with Ultraband, polypropylene, and polyester strapping from 5/8" up to 3/4" in width. To guarantee maximum performance right out of the box the strap type and size must be specified when ordering.



Included with the purchase of the tool you will receive two batteries and a charger.



Control Pad

Specifications

Length:	13.7" (350mm)
Width:	5.1" (130mm)
Height:	6.5" (165mm)
Strap Type:	Ultraband, PP and PET
Seal Type:	Friction Weld
Weld Efficiency:	Up to 85%

Package Size:	Min. Flat Package is 4.7" Min. Round Package Diameter is 27.5"
Strap Width:	5/8" (15mm) to 3/4" (19mm)
Strap Thickness:	.031" (.8mm) to .050" (1.27mm)
Max. Tension:	765 lbs.
Weight (w/battery):	8.3 lbs.

5740 Bayside Road, Virginia Beach, VA 23455

Phone: (800) 526-0827 Fax: (757) 363-8016

E-mail: order@dynaric.com Web address: www.dynaric.com