

DF-20L Semi-Automatic Low Table Strapping Machine

Features and Benefits


- Operates on 115 volt single phase power
- Widest available adjustable tension range
- 6mm,9mm or 12mm strapping can be used
- Fast cycle time
- Audible cycle alert safety signal (ACASS) system
- Strap feed and tension externally controlled
- Minimal maintenance and lubrication required
- Casters allow for easy movement within your facility
- Limited number of moving parts
- Quick release feed wheel system for easy clearing and cleaning
- Dispenser braking system with no belts to wear out or adjust
- Complete accessibility for maintenance
- Six month warranty on parts
- Equipped with a hinged table top for greater accessibility



Dynaric, Inc.



DF-20L Semi-Automatic Low Table Strapping Machine



SPECIFICATIONS

Overall Width:	21.9" (555mm)
Overall Length:	53.1" (1350mm)
Overall Height:	23.2" (590mm)
Table Height:	13.7" (350mm)
Machine Weight:	143 lbs.
Sealing Method:	Heat Seal
Seal Head Location:	Bottom: 9.25" (240mm) in from the right hand edge
Power Supply:	115 volt, single phase
Cycle Time:	2.0 seconds
Cycle Initiation:	Strap insertion with "ACASS" System

Tension:	External electronic adjustable control: 6-120 lbs.
Min. Package Size:	4" (102mm) x 2.4" (61mm) (H x W)
Max. Package Wt.:	180 lbs.
Mobility:	(5) Casters, two of which are locking
Strapping Size:	6mm, 9mm or 12mm (a simple guide change and adjustment is required*)
Table Size:	29.9" (760mm) x 21.9" (555mm) (L x W)
Dispenser:	9" (229mm) I.D. / 8" (203mm) Face / 18" (457mm) O.D.* 8" (203mm) I.D. / 8" (203mm) Face / 18" (203mm) O.D.*

* Must specify when ordering.